

### SPECIFICATIONS .

For masonry pools from  $2.5 \times 3$  m up to  $8 \times 15$  m + 3 m step unit For all types of pool whether new build or refurbishment.

- 1 Immersed pit. 3 possiibilities : decking in exotic wood IPE, Robinia or dark grey composite to be in perfect harmony with the pool edge covering.
- 2 Tubular motorisation perfectly adapted to refurbishment. 120 or, 250 Nm motors depending on the pool size. Remote control using a key operated switch.

Torque limiter: used to stop the opening of the cover if an abnormal strain is detected on it.

Remotely controlled by Wi-Key, the remote wireless control box.


- 3 White, beige or grey lacquered aluminium beam.
- 4 Composite plate.
- Cover composed of opaque PVC or polycarbonate solar slats fitted with locking kits. Slats available in several colors for perfect matching with your environment.


### **OPTIONS**

Securiwall, a PVC separating wall between the pit and the pool.

For pools up to 7m width and 2.07m deep, whatever the bottom profile.

Available in white, grey or beige.





ROLLENERGY EVOLUTION IS AN IN-GROUND COVER SUITABLE FOR ALL TYPES OF POOL WHETHER NEW BUILD OR REFURBISHMENT.

THANKS TO ITS TUBULAR MOTORISATION IT IS EASIER TO INSTALL AND REQUIRES NO STRUCTURAL WORK.

### **DISCRETION**

Perfectly suited to indoor and outdoor pools, Rollenergy Evolution disappears completely into its pit when open, thus becoming invisible. Its cover available in several colours and a wide selection of wood or composite decking makes it possible to harmonise its style with the

### **VERSATILITY**

Thanks to its tubular immersed watertight motor, Rollenergy Evolution requires no structural works and thus adapts to all types of masonry pools whether for new build or for refurbishment.
Its standard electric control box includes salt water chlorinator management, making it possible

### **ECO-RESPONSIBLE**

Covering your pool with a Rollenergy Evolution safety cover limits evaporation, which is the cause of drops in water levels, while maintaining the pool temperature and limiting external pollution. Available with polycarbonate solar slats, Rollenergy Evolution makes it possible to heat the water naturally and make



# THE WIRELESS REMOTE CONTROL BOX




- Pool opening and closure information is sent using digital wireless communications.
- No connections or cable passages.
- An aesthetic and watertight control box for indoor or outdoor installations.
- Use secured by a password and compliant with the NF P 90-308 safety standard.





SLATS .

## NEW **IVERNEA**



















### Polycarbonate solar slats

Compliant with the NF P 90-308 standard (DEL exclusivity)

5 available colours (brown, crystal, green, blue, black, silver\*)














Compliant with the NF P 90-308 standard 4 available colours (medium grey 2, white, beige, blue)

### **MAXIMUM SAFETY**



The purpose of DEL safety covers is not to replace the vigilance of parents and/or responsible adults which remains the essential factor for the safety of young children. DEL automatic covers are safety covers designed to prevent children under 5 years old from accessing the pool. A child can drown in under 3 minutes, no type of protective measure can replace the monitoring and vigilance of a responsible adult.

#### Please read carefully and keep in a safe place.

Rollenergy is a pool safety cover designed to prevent children under 5 years old from accessing the pool. This product complies with the NF P 90-308 standard It is not a substitute for common sense or personal responsibility. The purpose of this cover is not to replace the vigilance of parents and/or responsible adults which remains the essential factor for the safety of young children. A child can drown in under 3 minutes, no type of protective measure can replace the monitoring and vigilance of a responsible adult. Guarantee: 3 years for the motor and slats, 2 years for roller in compliance with our general sales terms and conditions. Manufacture sheet: For the cover to be correctly fitted to the pool it is essential to supply a drawing of the pool with measurements taken every metre. In compliance with standard NF P 90-308, the gap between the inside of the pool and the edge of the cover must be less than 70 mm. Manoeuvre time: 3 minutes for automatic opening or closure plus 30 seconds to lock or unlock the safety locking system. Rollenergy can be opened and closed by a single person. Use: in all seasons. For the cover to operate correctly maintain a constant water level corresponding to normal pool filtering. It is essential to fit a water level regulator. The water level must be compliant with the instructions. Use limitations: The installation of an automatic DEL cover on overflow pools and/or pools with steps on the length side (removable steps on the side) is not compliant with standard NFP 90-308. In this case please use other compliant equipment. Unless otherwise specified by the manufacturer, immersion alarms are not compatible with DEL automatic covers. Wintering: Close the pool for winter depending on the geographic location. Without lowering the water level, close the cover in the safety position and eventually install a wintering net to protect the cover. If the water level is dropped to put the parts to insert above the water line, roll the cover and secure the pool using a safety wintering cover. Packing list For 5 x 10 m pool. Slats: 4 packs of 5.10 x 0.25 x 0.20 m. Tube: 1 pack 4.948 x Ø 0.16 m. Beam: 1 pack of 5.1 x 0.17 x 0.12 m. Decking : 1 pallet 1.20 m x 1.00 m x 0.50 m. Motorisation kit: 1 pack of 0.62 x 0.35 x 0.35 m. Weight: 350 kg. Securiwall: 1 pack of 5.00 x 0.25 x 1.27 m. Weight: 77kg.

For more information about your project ask your pool professional for advice.

Distributor's stamp