# **DATA SHEET**



C.P.A. S.R.L.

# **AUTOCHLOR RP**





## **Description - Version RP**

- High efficiency electrolytic generation system
- High rate of chlorine production for each unit
- Cell self-cleaning system by polarity inversion
- Simplified installation
- Small size and light weight of the device
- Easy maintenance and cleaning of the cell
- Salt concentration in the pool 4.2 / 4.5 kg of salt / m³ of water







Medium cell / large

#### Main technical features

Code	Description	Clorogas	Pools till to	Raccomende d flow	Electrica l use	Power Supply 50 Hz	Weig ht	Dimensions
		[g/h]	[m³]	[l/min]	[kW]	[V]	[kg]	[mm]
1075040	Autochlor RP 15	15	75	150-450	0,153	220-240	11	370x310x220
1075031	Autochlor RP 20	20	90	150-450	0,227	220-240	11	370x310x220
1075041	Autochlor RP 25	25	120	150-450	0,206	220-240	11	370x310x220
1075032	Autochlor RP 36	36	170	150-450	0,234	220-240	11	370x310x220
1075033	Autochlor RP 50	50	230	150-450	0,388	220-240	27	430x330x280
1075034	Autochlor RP 64	64	300	150-450	0,525	220-240	27	430x330x270
1075036	Autochlor RP 100	100	450	150-450	1,130	220-240	27	650x600x300

### **WARNING:**

• C.P.A. s.r.l. recommends the use of refined, recrystallized salt of boiling at high solubility as per the following table.

1075018	Special pool salt in tablets - 25 kg bag
1075019	Special granular pool salt - 25 kg bag
1055234	Trousse sale - 10 Strips

• C.P.A. s.r.l. recommends the installation of the anode for protection against galvanic corrosion of elements metal in systems with electrolytic treatment. Wear of the anode is to be verified periodically.

500000	Magnesium anode ø1 "- Male connection 1" - Length 50 mm			
	5			
500001	Magnesium anode ø1 "- Male connection 1" - Length 110 mm			

#### Note

- The information contained in this document may vary at the discretion of the editor, without notice, together with the changes to the product in question in this document: it will be
- the customer's responsibility when placing the order to verify the persistent correspondence of the product to the information sheet.
- Any images and technical diagrams reproduced in this document have a purely informative value and are not valid for contractual purposes.