



## **TECHNICAL NOTE: laying of poolside and tiles**

- a. In relation to the type of processing envisaged, it is advisable to present the edge or the flooring dry in order to verify the presence of any defects, incongruities and / or discrepancies with respect to what is foreseen in the project.
- b. Based on the "chromatic" or "decorative" needs, it is the installer's responsibility to use pieces from the same supply, selecting the product, in order to mitigate any differences in shades due to its composition.
- c. The laying surface must be sufficiently compact, flat and clean; and having reached complete "maturation". This plan must also take into account all necessary precautions to prevent lack of resistance, in order to guarantee the support function.
- d. As "glue" to use a professional product, suitable for outdoor use, chromatically similar to the material supplied, following the precautions listed in the relevant technical data sheet.
- e. And. Before proceeding with the installation, clean the edges and tiles with dry rags. If necessary, use tap water to moisten the rags. Never use abrasive cloths or similar.
- f. Edges or tiles must be laid with grouted joints, with a product suitable for outdoor use, in the presence of chemically treated water for swimming pools and chromatically similar to the material supplied.
- g. If the installation is NOT done as a last job, protect edges and tiles with special painter's sheets, in order to avoid soiling, trampling marks and more generally various damage due to the construction site. Alternatively, carry out a thorough cleaning with a detergent, wax remover and degreaser.
- h. At the end of the installation, clean the whole with a concentrated neutral detergent product. Then treat the flooring with a breathable water-repellent product, the choice of which is the sole responsibility of the installer.
- i. the. Any streaks detectable on freshly laid samples must be reviewed over a period of six months, a time deemed adequate for the end of the material's maturation cycle.

## **MAINTENANCE: poolside and tiles**

- 1. Evitare l'accumulo di sporcizia insistente: è consigliata la pulizia della pavimentazione con cadenza regolare in funzione del contesto e dell'esposizione.
- 2. L'eventuale pulizia NON dovrà avvenire con getti ad elevata pressione e/o con l'impiego di sostanze aggressive chimicamente attive che potrebbero essere causa di danni rilevanti. In tale caso il fornitore NON si assume responsabilità alcuna in ordine a danneggiamenti così provocati.
- 3. All'occorrenza ed in base al contesto ambientale, potrebbe risultare consigliabile l'uso di prodotto detergente, decerante e sgrassante.
- 4. Nel caso di formazione di ghiaccio sui bordi, NON utilizzare assolutamente sale, né acqua calda o prodotti anti-gelo.